

TYDAN TDS

Commercial Lighting / Batten, Cleanroom, Specialist Lighting



Features

- Class ISO 3 certified to DIN EN ISO 14644-1 (Equivalent to FED STD 209E Class 1)
- Slim teardrop profile for cleanroom environment
- IP54 suitable for wet environment
- External cable coupler for easy installation
- Designed for end-to-end mounting
- Robust extruded aluminium body & corrosion resistant
- Long life, low energy consumption, no product maintenance is required
- PC extruded diffuser and end cap
- Wide distribution beam



Applications

- Industrial cleanrooms
- Healthcare facilities
- Food & Pharmaceutical industries

Option

- Dimmable
- Amber (610nm)


Standards

- Manufactured under ISO 9001:2015 to standards
- IEC/AS/NZS 60598.1
- IEC/AS/NZS 60598.2.1
- IEC/AS/NZS CISPR 15
- DIN EN ISO 14694-14 CLASS ISO 13

Mounting



Surface mounted



TYDAN TDS

Commercial Lighting / Batten, Cleanroom, Specialist Lighting



Product Code Key

Model	Length	Power	-	CRI & Colour Temp.	Dimming
TDS	2 = 650	15 = 15W		R84 = CRI>80, 4000K	D07 = 0-10V Dimming
	4 = 1250	20 = 20W		R87 = CRI>80, 6500K	D10 = DALI Dimming
		35 = 35W		R61 = Amber (610nm)	
	5 = 1550	25 = 25W		(only applicable for TDS215 & TDS420)	
		50 = 50W			

e.g. TDS435-R61 = Tydan TDS series, 1200mm, 35W, Amber (610nm)

Specifications

Model	TDS215-Rx	TDS420-Rx	TDS435-Rx	TDS525-Rx	TDS550-Rx
Length (mm)	650	1250	1250	1550	1550
Nominal Power (W)	15	20	35	25	50
Luminaire Flux (lm)	2025	2700	4725	3375	6750
Luminaire Efficacy (lm/W)	135 (Dimming = 130)				
CCT (K)	4000/6500				
Input Voltage (V)	220-240				
CRI (Ra)	>80				
Frequency (Hz)	50/60				
Luminaire Rated Life (hr)	>50,000				
Operating Temp. (°C)	-20 to 40				
IP Rating	IP54				
IK Rating	IK03				
Power Factor	>0.9				
SDCM	<5				
Beam angle (°)	180°				
Colour	White (Amber only for R61)				
Weight (kg)	0.70	1.40	1.40	1.74	1.74


"x" denotes CRI & CCT, R84 = CRI>80, 4000K ; R87 = CRI>80, 6500K ; R61 = Amber (610nm)

TYDAN TDS


Commercial Lighting / Batten, Cleanroom, Specialist Lighting



Lighting Data



Dimensions



davislighting.com davislighting.com.au

All photometric and electrical data published are of $\pm 10\%$ tolerance. Characteristics and specifications may change without notice. All electrical installations / connections should be carried out by a suitably qualified person. Application images are indicative only and may not contain actual Davis product. The information contained in this publication is typical and must not be interpreted as a guarantee of individual product performance. Please contact the nearest Davis Lighting Sales Office or check our website for the latest product specifications.

Copyright © 2023 Davis Lighting. All Rights Reserved.