



# FLORENZO FLZ

**Efficient floodlight with tempered glass for durability and instant turn-on capability, ensuring immediate and versatile illumination.**

# FLORENZO FLZ

## Floodlight



### Features

- Modern and elegant design
- Durable and slim aluminium die-cast housing
- Tempered glass cover
- Instant turn on
- IP66 and IK08 rating
- Flexible conduit for cable protection
- Integrated or remote gear
- Surge protection: 20kV

### Applications

- Industrial
- Recreation
- Urban & Building

### Options

- Distribution: 7 types
- Visor
- 0-10V + DMX dimming
- DALI Dimming
- DMX Dimming

### Standards

- IEC 60598-2-5
- IEC/AS/NZS 60598.1
- IEC/AS/NZS CISPR 15
- Manufactured under ISO 9001:2015 standards

### Mounting Methods



Pole Mount

# FLORENZO FLZ

Floodlight



## Product Code Key

Model	Power	Remote type	- CRI & CCT	Dimming	Distribution type
FLZ	<b>600</b> =600w <b>800</b> =800w <b>1K0</b> =1000w <b>1K2</b> =1200w	<b>A</b> =Remote with gear tray <b>B</b> =Remote with gear box  (omit for integrated)	<b>R83</b> =CRI>80, 3000K <b>R84</b> =CRI>80, 4000K <b>R85</b> =CRI>80, 5000K	<b>D07</b> =0-10v (for remote gear only) <b>D08</b> =1-10v (for integrated only) <b>D10</b> =DALI (for integrated only)	<b>Z1</b> =12° <b>Z2</b> =Type I-VS <b>Z3</b> =Type IV-VS <b>Z4</b> =30° <b>Z5</b> =45° <b>Z6</b> =60° <b>Z7</b> =Type II-VS

eg: **FLZ1K2B-R85D07Z7** = FLZ 1200W, remote gear box with 0-10v driver, CRI>80, 5000K, with Type II-VS distribution

## Specifications

FLORENZO FLZ	FLZ600	FLZ800	FLZ1K0	FLZ1K2
Nominal Power (W)	600	800	1000	1200
Input Voltage (V)	220-240			
Frequency (Hz)	50/60			
Luminous Flux (lm)	90000	120000	150000	180000
Efficacy (lm/W)	150			
CRI	≥80			
Power Factor	>0.9			
SDCM	≤5			
CCT (K)	3000/4000/5000			
Product Lifetime (L70B50)	>50000			
Operating Temp. (°C)	-30 to 40			
Weight (kg)	26	29.8	33.2	
IP Rating	IP66			
Product Carton qty per box	1			
Product Carton Dimension (mm)	855 x 695 x 430			
Product Carton Weight for integrated gear (kg)	37		41	
Product Carton Weight for remote gear A & B (kg)	37		41	

\*Data shown are integrated version


# FLORENZO FLZ

Floodlight




## Lighting Distribution


FLZ800A-R85D08Z1



FLZ800A-R85D08Z2




FLZ800A-R85D08Z3




## Dimensions

FLZ600 / FLZ800



FLZ1K0 / FLZ1K2




# FLORENZO FLZ


Floodlight





FLZ600A / FLZ800A / FLZ600B / FLZ800B





FLZ1K0A / FLZ1K2A / FLZ1K0B / FLZ1K2B



Gear Tray with Remote Driver for FLZ...A



Gear Box with Remote Driver for FLZ...B




# FLORENZO FLZ


Floodlight



FLZ 600W-800W(without driver)



FLZ 1000W-1200W(without driver)



davislighting.com davislighting.com.au

All photometric and electrical data published are of  $\pm 10\%$  tolerance. Characteristics and specifications may change without notice. All electrical installations / connections should be carried out by a suitably qualified person. Application images are indicative only and may not contain actual Davis product. The information contained in this publication is typical and must not be interpreted as a guarantee of individual product performance.

Generated on: 10-03-2025. Please contact the nearest Davis Lighting Sales Office or check our website for the latest product specifications.