

This installation guide is valid for the following models:

- SABER LED



PRIOR TO INSTALLATION



- Read all instructions to prevent injury, electric shock or damage due to fire or mechanical hazards
- See product label for supply specifications.



- Suitable for direct mounting on flammable surfaces.

- Inspect the luminaire and associated parts for any signs of defect, in particular fasteners, cables and the diffuser or glass lens
- Consult with the supplier / sales office for details regarding replacement
- **DO NOT INSTALL THE LUMINAIRE IF IT APPEARS IN ANY WAY FAULTY**





CAUTION




- Installation is to be completed by a competent licensed electrician, in accordance with these instructions and relevant local regulations.
- Electronic control equipment must not be subjected to high voltages, DO NOT MEGGER between Live and Neutral.
- All cable/conduit terminations must be installed in accordance with the designated IP rating of this product.
- Suitable installation fastening methods should be employed to ensure the mounting points are not damaged when subjected to vibration and or movement.
- The light source contained in this luminaire shall only be replaced by the manufacturer or his service agent or similar qualified person.
- When using glands provided as cord anchorage for flexible cable the cable diameter shall not be less than 8.4 mm and not larger than 12 mm.

DIMENSIONS




INSTALLATION


1. Turn OFF power




2. Loosen end cap screws which will allow end cap to tilt outwards (whilst still attached to the fitting). Remove diffuser.




3. Slide out the diffuser from the end cap and completely detach it from the fixture.




4. Proceed to loosen the two screws securing the LED tray.



5. Gently remove the LED tray, ensuring proper safety measures such as using a lanyard or disconnecting the DC connector.



6. Connect the mains cable wires to the terminal block securely, following the wiring diagram below. Afterward, tighten the screws on the cable clips. To reverse the cycle, follow the steps in reverse order: 5, 4, 3, 2, 1, as illustrated in the image.





Unauthorized modification & improper installation void product warranty

MAINTENANCE

The supply must be isolated before opening or accessing the luminaire. Product maintenance is critical to the products designed performance. Davis Lighting is not responsible for any product not maintained in accordance with the recommended procedure or intervals. It is recommended that a bi-annual cleaning cycle is implemented. Inspect optical surfaces for damage or crack. Products supplied with visors or covers must not be operated with a damaged visor or cover; it is recommended damaged visors or covers be replaced by a competent person immediately. Seals and electrical components such as wirings to be checked for deterioration.



All photometric and electrical data published are of $\pm 10\%$ tolerance. Characteristics and specifications may change without notice. All electrical installations / connections should be carried out by a suitably qualified person. Application images are indicative only and may not contain actual Davis product. The information contained in this publication is typical and must not be interpreted as a guarantee of individual product performance.



This product may contain substances that can be hazardous to the environment if not disposed of correctly. Electrical and electronic equipment should never be discarded along with general waste but should be separated for correct treatment and recovery. Packaging and waste materials should be recycled wherever possible.